

Material Safety Data Sheet 1100/105

MSDB 1-3:

Silver/Copper - Phosphorus



Metalli as

Materiale Safety Data Sheet (MSDB)

@ Copyright, Metalli as, 2015



MSDB 1-3 Side 1 af 5 June 2015

	INDEX AND REVISION STATUS	
MSDB	TYPES OF MATERIALS	REVISED
1 - 1	SILVER BRAZING FILLER METALS (METALLI RANGE)	JUNI 15
1 - 2	SILVER BRAZING FOR SPECIAL APPLICATIONS	JUNI 15
1 - 3	SILVER/COPPER - PHOSPHORUS	JUNI 15
1 - 4	SOFT SOLDERS	JUNI 15
1 - 5	BRONZE FILLER METALS	JUNI 15
1-6	FLUX COATED RODS	JUNI 15

Metalli as

Material Safety Data Sheet @ Copyright, Metalli as 2015

> MSDB 1-3 Side 2 af 5 June 2015

This data is made i.h.t Commission Directives 91/155/EEC, 93/112/EEC & S.I. 1993 No. 1746

1.1 IDENTIFICTION OF SUBSTANCE

This Product Safety Data Sheet gives specific information on Cadmium free Silver/Copper - Phosphorus alloys.

Silver/Copper - Phosphorus

1.2 SUPPLIER

Metalli as

Nyholms Alle 46

DK-2610 Rødovre

Danmark

Tlf: +45 36 70 05 44

Fax: +45 36 70 78 79

E-mail: info@metalli.dk

Home: www.metalli.dk

2. COMPOSITION

The only potential health hazards involved with this product arise from its use. On heating, metal and metal oxide fumes may be evolved but are unlikely to exceed the above stated OES's under normal conditions. However, severe overheating could lead to the emission of fumes in harmful concentrations. Metal fumes fever can be caused by exposure to excessive fumes of copper and zinc oxide. Symptoms are similar to those of influenza and often appear after a latent period of up to 10 hours. They normally disappear after 24 hours with rest.

3. HAZARD IDENTIFICATION

					Melting	
Alloy	Ag	Cu	Р	Others	Range C	ISO 17672
Metalli 18 P	17,75	75	7,25	-	644	CuP 285
Metalli 15 P	14,5	80,85	4,65	-	644-800	CuP 284
Metalli 6 P	6	86,75	7,25	-	644-718	CuP 283
Metalli 5 P	5	89	6	-	644-815	CuP 281
Metalli 2 P	2	91,5	6,5	-	644-825	CuP 279
Metalli Cu 1	-	92,6	7,4	-	714-810	
Metalli Cu 2	-	92	6	2,0 Antimony	690-825	CuP 389
Metalli Cu 3	-	93,8	6,2		714-890	CuP 179

^{*} Time weighted Average

^{**} under review

^{***}Maximum Exposure Level



MSDB 1-3 Side 3 af 5 June 2015

4. FIRST AID MEASURES

Metal oxide fume can be irritating to the upper respiratory tract, nose and throat. In powder form, metal dust will irritate the eyes and is harmful if ingested.

Inhalation Fume may be evolved at brazing temperatures, which will irritate nose, throat and

respiratory organs. Remove patient to fresh air. In acute cases, apply artificial respiration.

Summon medical aid if necessary.

Ingestion Not applicable. However, if the alloy in powder form is ingested, rinse mouth with water and

Give patient water or milk to drink. Do not induce vomiting. Summon medical aid.

Eyes Not applicable. However, if the alloy is in powder form and dust gets into the eyes, irrigate

with water or isotonic saline for up to 20 minutes. Seek medical attention if there is any hint

of eye damage.

Skin Wash hands with soap and water after handling brazing alloy. If any skin irritation develops,

seek medical advice.

5. FIRE FIGHTING MEASURES

Non-flammable. Use extinguishing medium suitable for surrounding fire but exercise care with water if molten metal is present. Use full personal protection with breathing apparatus in a fire as harmful fumes may be evolved from the molten alloy.

6. ACCIDENTAL RELEASE MEASURES

Material may be collected for re-use or scrap as required. If alloy is in powder, form avoid getting dust in the eyes or breathing metal dust.

7. HANDLING AND STORAGE

Handling: Use in a well ventilated area or with local extraction systems. Do not inhale any fumes

evolved during use. Wash hands thoroughly with soap and water after handling the brazing

alloy, particularly before eating or smoking.

Storage: No special requirements – store in cool, dry conditions. Keep powder containers closed.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION



MSDB 1-3 Side 4 af 5 June 2015

		Long term 8-	Short Term 15
	Element	hours TWA*	minute Value
**	Silver	0.1 mg/m3	-
	Copper Fume (as Copper)	0.2 mg/m3	-
	Tin compound inorganic (as Tin)	2.0 mg/m3	4.0 mg/m3
	Antimony nd compound	0,5 mg/m3	-
	Disphosphorus pentoxide	-	2,0 mg/ m3

^{*}Time Weighted Average

Avoid exposure to fume with good ventilation or local extraction. If a risk of inhalation exists, personal respiratory protection should be worn. Safety glasses should be worn as well as gloves if required. Wash hands after using this material. The use of protective clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Silver/copper/Brass coloured metal depending on composition.

Odour None

pH Not applicable.

Melting point As shown in Section 3.

Flash point Not applicable. Flammability Non flammable.

10. STABILITY AND REACTIVITY

No reaction with air or water. Avoid contact with acids.

11. TOXICOLOGICAL DATA

Material not classified as toxic. No other data avaiblablee.

12. ECOLOGICAL INFORMATION

As far as is known, no threat is posed to the environment by this material.

13. DISPOSAL CONSIDERATIONS

According to local and national regulations. Recommended method: as scrap for refining.

14. TRANSPORT INFORMATION

Not classified for land, sea or air transport. No UN No/s have been issued for these alloys.

^{**}Under review

^{***}Maximum Exposure Level



MSDB 1-3 Side 5 af 5 June 2015

15. REGULATORY INFORMATION

Material classification		Harmful
Risk Phrases	R20	Harmful by inhalation
Safety Phrases	S20/21	When using do not eat, drink or smoke.
	S23	Do not breathe fumes
	S36/37/39	Wear suitable protective clothing, gloves and eye/face
		Protection.
	S38	In case of insufficient ventilation wear suitable respiratory
		Equipment.

On label alloy is stated to be "Cadmium Free". Users are warned that on heating product may give off fumes hazardous to health and to use adequate ventilation.

16. OTHER INFORMATION

Metalli Data sheet 1100:105 "Health and Safety in Brazing".

Guidance Note EH54 "Assessment of Exposure to fume welding and allied processes" HSE 1990 Guidance Note EH55 "The control of exposure to fume from welding, brazing and similar processes" HSE 1990.

Guidance Note EH60 "Nickel and inorganic compounds: health and safety precautions HSE 1991.