

Material Safety Data Sheet 1100/105

MSDB 1-5:

Bronze Filler Metals



Metalli as

Material Safety Data Sheet (MSDB)

@ Copyright, Metalli as, 2015

Metalli as

Material Safety Data Sheet
@ Copyright, Metalli as 2015

MSDB 1-5
Side 1 af 5
June 2015

INDEX AND REVISION STATUS

<u>MSDB</u>	<u>TYPES OF MATERIALS</u>	<u>REVISED</u>
1 - 1	SILVER BRAZING FILLER METALS (METALLI RANGE)	JUNI 15
1 - 2	SILVER BRAZING FOR SPECIAL APPLICATIONS	JUNI 15
1 - 3	SILVER/COPPER - PHOSPHORUS	JUNI 15
1 - 4	SOFT SOLDERS	JUNI 15
1 - 5	BRONZE FILLER METALS	JUNI 15
1 - 6	FLUX COATED RODS	JUNI 15

Metalli as

Material Safety Data Sheet
@ Copyright, Metalli as 2015

MSDB 1-5
Side 2 af 5
June 2015

This data is made i.h.t Commission Directives 91/155/EEC, 93/112/EEC & S.I. 1993 No. 1746

1.1 IDENTIFICATION OF SUBSTANCE

This Product Safety Data Sheet gives specific information on Cadmium free Bronze Filler metals.

Bronze Filler Metals

1.2 SUPPLIER

Metalli as
Nyholms Alle 46
DK-2610 Rødovre
Danmark

Tlf: +45 36 70 05 44
Fax: +45 36 70 78 79
E-mail: info@metalli.dk
Home: www.metalli.dk

2. COMPOSITION

Bronze filler metals	Composition									Melting range°C	gram/cm3
	Cu	Sn	Ni	Si	Mn	Co	B	Zn	Fe		
METALLI Bronze B	97		2,95				0,05			1081 - 1101	8,9
METALLI Bronze F	57,5				2	2		38,5		890 - 930	8,2
METALLI Bronze G	96,8		2,6	0,6						1090 - 1100	8,9
METALLI B - 720	59	1		0,15	0,5			Bal	0,5*	875 - 895	8,2
METALLI B - 721	57,5	0,9		0,2				Bal	2,4*	870 - 900	8,1
METALLI B - 7503V	48,5		9,5	0,2				Bal	0,2	890 - 910	8,2

. = incl in Ni

Metalli as

Material Safety Data Sheet
@ Copyright, Metalli as 2015

MSDB 1-5
Side 3 af 5
June 2015

3. HAZARD IDENTIFICATION

The only potential health hazards involved with this product arise from its use. On heating, metal end metal oxide fumes may be evolved but are unlikely to exceed the above stated OES's under normal conditions. However, severe overheating could lead to the emission of fumes in harmful concentrations. Metal fume fever can be caused by exposure to excessive fumes of copper and zinc oxide. Symptoms are similar to those of influenza and often appear after a latent period of up to 10 hours. They normally disappear after 24 hours with rest.

4. FIRST AID MEASURES

Metal oxide fume can be irritating to the upper respiratory tract, nose and throat. In powder form, metal dust will irritate the eyes and is harmful if ingested.

- | | |
|------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inhalation | Fume may be evolved at brazing temperatures, which will irritate nose, throat and respiratory organs. Remove patient to fresh air. In acute cases, apply artificial respiration. Summon medical aid if necessary. |
| Ingestion | Not applicable. However, if the alloy in powder form is ingested, rinse mouth with water and Give patient water or milk to drink. Do not induce vomiting. Summon medical aid. |
| Eyes | Not applicable. However, if the alloy is in powder form and dust gets into the eyes, irrigate with water or isotonic saline for up to 20 minutes. Seek medical attention if there is any hint of eye damage. |
| Skin | Wash hands with soap and water after handling brazing alloy. If ay skin irritation develops, seek medical advice. |

5. FIRE FIGHTING MEASURES

Non-flammable. Use extinguishing medium suitable for surrounding fire but exercise care with water if molten metal is present. Use full personal protection with breathing apparatus in a fire as harmful fumes may be evolved from the molten alloy.

6. ACCIDENTAL RELEASE MEASURES

Material may be collected for re-use or scrap as required. If alloy is in powder, form avoid getting dust in the eyes or breathing metal dust.

7. HANDLING AND STORAGE

Metalli as

Material Safety Data Sheet
@ Copyright, Metalli as 2015

MSDB 1-5
Side 4 af 5
June 2015

Handling: Use in a well ventilated area or with local extraction systems. Do not inhale any fumes evolved during use. Wash hands thoroughly with soap and water after handling the brazing alloy, particularly before eating or smoking.

Storage: No special requirements – store in cool, dry conditions. Keep powder containers closed.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

UK Occupational Exposure Standards Are:

Element	Long Term 8-hour TWA* Value	Short Term 15 minute Value
**Silver	0,1 mg/m ³	-
Cobber fume (as Cobber)	0,2 mg/m ³	-
Tin compound inorganic (as Tin)	2,0 mg/m ³	4,0 mg/ m ³
Antimony and compounds	0,5 mg/m ³	3,0 mg/m ³
Diphosphorus pentoxide	-	2,0 mg/m ³

*Time weighted Average

** Under review

*** Maximum Exposure Level

Avoid exposure to fume with good ventilation or local extraction. If a risk of inhalation exists, personal respiratory protection should be worn. Safety glasses should be worn as well as gloves if required. Wash hands after using this material. The use of protective clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Silver/copper/Brass coloured metal depending on composition.
Odour	None.
pH	Not applicable.
Melting point	As shown in Section 2.
Flash point	Not applicable.
Flammability	Non flammable.

10. STABILITY AND REACTIVITY

No reaction with air or water. Avoid contact with acids.

11. TOXICOLOGICAL DATA

Material not classified as toxic. No other data available.

12. ECOLOGICAL INFORMATION

Metalli as

Material Safety Data Sheet
@ Copyright, Metalli as 2015

MSDB 1-5
Side 5 af 5
June 2015

As far as is known, no threat is posed to the environment by this material.

13. DISPOSAL CONSIDERATIONS

According to local and national regulations. Recommended method: as scrap for refining.

14. TRANSPORT INFORMATION

Not classified for land, sea or air transport. No UN No/s have been issued for these alloys.

15. REGULATORY INFORMATION

Material classification	Harmful	
Risk Phrases	R20	Harmful by inhalation
Safety Phrases	S20/21	When using, do not eat, drink or smoke.
	S23	Do not breathe fumes
	S36/37/39	Wear suitable protective clothing, gloves and eye/face Protection.
	S38	In case of insufficient ventilation wear suitable respiratory Equipment.

On label alloy is stated to be "Cadmium Free". Users are warned that on heating product may give off fumes hazardous to health and to use adequate ventilation.

16. OTHER INFORMATION

Metalli Data sheet 1100:105 "Health and Safety in Brazing".

Guidance Note EH54 "Assessment of Exposure to fume welding and allied processes" HSE 1990

Guidance Note EH55 "The control of exposure to fume from welding, brazing and similar processes" HSE 1990.